



Mondial Group s.r.l.

S.S.31 n.34 I5040 Mirabello Monferrato (AL) - IT

Tel. +39 0142/478 211

Fax +39 0142/781 775

www.mondialgroup.it info@mondialgroup.it



2 VASCHE TTE DA 5 I.
2 BINS 5 I.
2 BACS 5 I.



4 VASCHE TTE DA 2,5 I.
4 BINS 2,5 I.
4 BACS 2,5 I.

Mini Cream & Mini Buffet

TOP DISPLAY COUNTERS FOR ICE CREAM AND YOGHURT IMPULSE SALES




100% MADE IN ITALY



Mini Cream & Mini Buffet

The best products for ice cream and

yoghurt exposition on buffets



- Totally customizable unit with digital printing on sheet metal.
- Low energy consumptions.
- Upper, flat, low emissivity glass with black silkscreen edge, easily cleaning.
- Very resistant gasket on the frame.
- Self – balancing glass top.
- External thermometer, led inside the tank with external switch (available without led in the tank, too).



MODELS IN DIFFERENT VERSIONS: MINI CREAM/BUFFET 2V LED LUXE:

Version with led light inside the tank and with led back-lighted canopy.

MINI CREAM/BUFFET 2V LED:

Version with led light inside the tank and without canopy.

MINI CREAM/BUFFET 2V:

Version without led light inside the tank and without canopy

Example of customization



HIGHLIGHTS
Gasket easy to take off for an easy cleaning



Technical data

WITH CANOPY



Capacity packaging yoghurt
MINI BUFFET 2V LED LUXE:
 dimension packaging Ø 72 - h 70 mm
 40 cups placed in two rows

MINI BUFFET 2V LED LUXE

Customizable back- led lighted canopy with switch (this canopy can be also mounted afterwards)



MINI CREAM 3V LED LUX
 On request and special production

3 Bins 5 l.

Led light



led tank light switch



Mechanical thermostat



Light box switch and mechanical thermometer



Mini Cream	-10° -22°C
Temperature	-10° -22°C
Voltage and Frequency	230 V~ 50 Hz
Gas	R600a
Net dimension	490 x 790 x 345 mm (l x p x h)
Packed dimension	590 x 890 x 375 mm (l x p x h)
Gross capacity	28 l
Net capacity	20 l
Gross weight	32.00 Kg
Net weight	28.00 Kg
Heat insulation	Rigid polyurethane foam "HCFC/CFC/HFC" free
External cabinet	White prepainted steel sheet
Cabinet bottom	Galvanized steel sheet
Inner tank	Stainless steel- AISI 304 BA
Power consumption	90 W
Consumption (24h)	1,8 kWh/24h
Condensator	Wire and tube - maintenance free with powered fan
Evaporator	Static evaporator wrapping the tank
Defrosting	Manual
Climatic class	EN 441 4 (30°C-55%RH) L1

Mini Buffet	+2° +4°C
Temperature	+2° +4°C
Voltage and Frequency	230 V~ 50 Hz
Gas	R600a
Net dimension	490 x 790 x 345 mm (l x p x h)
Packed dimension	590 x 890 x 375 mm (l x p x h)
Gross capacity	28 l
Net capacity	20 l
Gross weight	32.00 Kg
Net weight	28.00 Kg
Heat insulation	Rigid polyurethane foam "HCFC/CFC/HFC" free
External cabinet	White prepainted steel sheet
Cabinet bottom	Galvanized steel sheet
Inner tank	Stainless steel- AISI 304 BA
Power consumption	95 W
Consumption (24h)	0,8 kWh/24h
Condensator	Wire and tube - maintenance free with powered fan
Evaporator	Static evaporator wrapping the tank
Defrosting	Manual
Climatic class	EN 441 4 (30°C-55%RH) L1